



OUR PRODUCT RANGE

Motor oils

- ◆ Synthetic and mineral oils, for light petrol up to heavy diesel engines
- ◆ Two-stroke motor oils

Transmission oils

- ◆ Mineral and synthetic
- ◆ Multi grade, API GL4 & GL5
- ◆ ATF oils

Hydraulic liquids

- ◆ Filtered Hydraulic oils (Nas 6)
- ◆ Zinc-free and zinc-containing hydraulic oils
- ◆ Biodegradable oils
- ◆ Nonflammable hydraulic liquids

Specialities for the industry

- ◆ Compressor oils
- ◆ Compressed air lubrication
- ◆ General lubrication
- ◆ Transformer oils
- ◆ Gearbox oils
- ◆ Thermal oils
- ◆ White oils

Sprays

- ◆ Silicone sprays
- ◆ Sprocket & gear wheels
- ◆ Anticorrosion
- ◆ Tapping oils
- ◆ Brake cleaner
- ◆ Penetrating oils
- ◆ White grease
- ◆ Food grade quality
- ◆ PTFE

Winter products

- ◆ Antifreeze
- ◆ Coolants
- ◆ Windscreen washer fluids

Metalworking fluids

- ◆ Water miscible and neat oils for all ferrous and non-ferrous metals
- ◆ Forming oils
- ◆ Grinding fluids
- ◆ Rust preventive oils
- ◆ Vanishing oils
- ◆ Spray oils
- ◆ Slideway oils

Food-grade lubricants

- ◆ Lubricants for the food industry (USDA H1/NSF)

Greases

- ◆ Greases for bearings
- ◆ Multi purpose greases
- ◆ Greases with PTFE, graphite and MoS2 additives
- ◆ Biodegradable greases
- ◆ Greases for high temperatures
- ◆ Specialities

High quality range for motorcycles

- ◆ Oils for motor, transmission, fork and chains

Equipments

- ◆ Oil tanks
- ◆ Grease pumps
- ◆ Skimmers
- ◆ Refractometers
- ◆ Filtering devices
- ◆ Dosage pumps
- ◆ Hose reels
- ◆ Spill trays
- ◆ Oil cans
- ◆ Degreasing tanks

Agriculture & Forestry

- ◆ Chain saw oils
- ◆ Biodegradable oils and greases
- ◆ Two-stroke and four-stroke oils

Cleaning products

- ◆ Degreasing agents
- ◆ Hand soaps
- ◆ Oil absorbing granulates

UNIL LUBRICANTS SINCE 1903

BELGIUM

Bergensesteenweg 713
1600 Sint-Pieters-Leeuw
Tel. +32 (0)2 365 02 00
Fax +32 (0)2 360 01 12
info@unil.com
orders@unil.com

THE NETHERLANDS

Tel. +31 (0)72 744 00 33
Fax +31 (0)72 744 00 34
infol@unil.com
ordersnl@unil.com

www.unil.com



ISO 9001 - ISO 14001
Certified



GREASES

Info

Are you uncertain about the type of lubricant you need for your vehicles and machines? Contact our technical service department, we'll be pleased to help you choose the optimal product for you.

Help Line +32 (0) 2 365 02 00 or send us a mail at info@unil.com



GREASES

APPLICATIONS

COMPOSITION

FEATURES

		Thickener		Base oil		Color	Sustainability	Temperature	Mechanical stability	Water resistance	Extreme pressure power	Corrosion resistance
		Soap base	Drop point (°C)	Nature	Viscosity (cSt at 40°C)							
Polygrease	Polyurea grease used for long lubrication periods of slide and roller bearings working under extreme conditions.	Diurea	260	Synthetic ester	100	Light yellow	2	-40/+180	xxx	xxx	xxx	xxx
Alba +	Teflon based grease, especially developed for the lubrication of bearings working under heavy load conditions.	Lithium complex	250	Mineral	185	White	2	-30/+180	xxx	x	xxx	xx
Thermoplex	Universal long life grease suitable for joints, slide and roller bearings exposed to heavy loads and high temperatures.	Lithium complex	250	Mineral	185	Green	2	-20/+170	xxx	xx	xx	xxx
Supergrease 350	Multifunctional "extreme pressure" grease with exceptional adhesion. Remarkable resistance water, heavy loads and temperature variations.	Lithium-Calcium	180	Mineral	310	Blue	2	-20/+140	xxx	xxx	xxx	xxx
Caliopall	Extreme pressure grease for low-speed bearings exposed to heavy loads. Long life grease for extended lubrication intervals.	Lithium-Calcium	170 185	Mineral	700 500	Brown	0 2	-20/+110 -20/+130	xx	xxx	xxx	xx
Molith EP	High quality grease with molybdenedisulphide (MoS2) and graphite, with a remarkable resistance to shocks and heavy loads. This grease is recommended for excavation, mining and public works equipment.	Lithium	190	Mineral	95	Black	2	-20/+140	xxx	xx	xxx	xx
Grease EP/R	Multifunctional "extreme pressure" grease.	Lithium	190	Mineral	95	Amber	00/0/ 1/2/3	-20/+140	xx	x	xx	xx
HT 300	Bentone based grease resistant to very high temperatures and insoluble in water. This grease is ideal for low-speed bearing exposed to extreme pressure and temperature.	Bentone	Without	Mineral	460	Black	2	-15/+300	xx	x	xxx	xx
Polyfood	Extreme pressure grease for the lubrication of various equipments within the food industry (bearings, conveyors,...).	Calcium-complex	200	White mineral oil	90	White	00/2	-50/+150	xx	xxx	xxx	xxx
Alimenta	Bentone based grease, NSF/H1 homologated, especially developed for the food industry.	Bentone	Without	White mineral oil	80	White	2	-20/+200	xx	xx	xx	xx
Synbio Grease	Biodegradable, water-repellent grease recommended for all applications respecting the environment.	Lithium-Calcium	160	Synthetic and vegetable ester	45	Green	2	-18/+145	xx	xxx	xx	xxx